

## VISICRYL 8800



Rev. No. 00  
Date: 20/02/2024  
Page: 1/2

**Chemical Nature** : Based on Pure Acrylic technology to impart high water resistant properties. Suitable for stone coating and texture paints. Can be used as clear coat to impart wet glossy appearance to the coating.

### Properties

#### PRODUCT SPECIFICATIONS

Solid content, weight %	: 48 ± 1
Viscosity at 30°C	
Brookfield RVT, 5/20, Ps.	: 40 - 90
pH (1:1 with water)	: 7 – 9

#### OTHER PROPERTIES:

Minimum film forming temperature(°C)	: + 19
Particles size, average (micron )	: 0.1
Plasticizer content	: Free from plasticizer
Response to associative thickener	: Good
Specific gravity, 30 °C	: 1.03 ± 0.02
Mechanical stability	: Good

#### FILM PROPERTIES:

Appearance	: Clear, hard
Surface	: Non-tacky

#### COMPATIBILITY WITH (Polymer Emulsion)

: **Visicryl 8800** is miscible with non ionic & anionic emulsions. However, there is a chance that such mixing may affect the property of **Visicryl 8800**.

#### FILLERS

: **Visicryl 8800** has good compatibility with normal fillers used in high sheen paint formulation. Also the pigment compatibility is good and can be further increased by incorporating suitable dispersing agent.

## Application

**FIELD OF APPLICATION** : **Visicryl 8800** is suggested for surfaces like stone and texture paint as clear coat offering glossy effect.

**PROCESSING** : Coatings are generally made with high speed mixers by dispersing first fillers, pigments, wetting agents and auxiliaries. **Visicryl 8800** is added at the last let down stage.

- To achieve film formation at lower temperature adequate quantity of coalescing solvents are to be incorporated.
- For higher viscosity thickeners are recommended to be added
- Suitable defoamer in required quantity is to be added to take care of foam during processing.
- Biocides need to be included in the formulation to guard against micro-organism growth.

## Safety

General safety precautions such as goggles, gloves, and face shields should be used while handling **Visicryl 8346HG**. MSDS is provided for detailed information.

**Industrial Hygiene** : **Visicryl 8800** is not harmful for the purpose for which it is intended and processed. It may irritate skin and mucous membrane on prolonged contact.

**Labeling** : **Visicryl 8800** is non hazardous and doesn't contain substances which have implication for labeling under regulations.

**Storage** : **Visicryl 8800** has a shelf life of 6 months from the date of manufacture, provided it is stored under shade, away from direct heat and sunlight and well protected from freezing.

**Packing** : 240/220 Kg HDPE Drums.

---

### Disclaimer:

Note: The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other company's raw materials are also being used. The recommendations do not absolve the user from the obligation of investigation of the possibility of infringement of third parties' rights and, if

necessary, clarifying the positions. For more details contact email: [marketing@visen.net](mailto:marketing@visen.net)

© Copyright, Visen Industries Ltd. [www.visen.net](http://www.visen.net)